

X線窓用ベリリウム箔



MATERION

厚み仕様

	IF-1 (純度:99.8%)	PF-60 (99.0%)	PS-200 (98.5%)	IS-50M (99.0%)
Vaccum-Tight(*)	7.6 - 254μm	25.4 - 3175μm	127 - 6350μm	500 - 3200μm
Optically-Dense	5.08 - 254μm	25.4 - 3175μm	127 - 6350μm	-
As-Rolled	2.54 - 254μm	25.4 - 3175μm	127 - 6350μm	-

(*) Vaccum tight: Heリークテスト @ 1×10^{-9} atm-cc/sec

寸法公差仕様

	IF-1 (純度:99.8%)	PF-60 (99.0%)	PS-200 (98.5%)	IS-50M (99.0%)
厚み	2.5 ~ 22.9μ : +5/-0μ	25.4 ~ 508μ : +/-10%	127 ~ 254μ : +/-10%	508 ~ 635μ : +/-51μ
	22.9 ~ 48.3μ : +5/-2.5μ	533 ~ 838μ : +/-51μ	279 ~ 635μ : +/-51μ	660 ~ 1397μ : +/-76μ
	50.8 ~ 254μ : +/-10%	863 ~ 1753μ : +/-76μ	660 ~ 1397μ : +/-76μ	1422 ~ 1905μ : +/-102μ
		1778 ~ 2362μ : +/-102μ	1422 ~ 1905μ : +/-102μ	1930 ~ 3175μ : +/-152μ
		2388 ~ 3175μ : +/-127μ	1930 ~ 3175μ : +/-152μ	3200 ~ 6350μ : +/-254μ
直径	12.7 ~ 101.6mm : +/-0.08mm	12.7 ~ 152.4mm : +/-0.08mm	0 ~ 152.4mm : +/-0.08mm 152.4 ~ : +/-0.13mm	-
長さ / 幅	0 ~ 76.2mm : +/-0.38mm	0 ~ 76.2mm : +/-0.38mm	0 ~ 76.2mm : +/-0.38mm	-
	76.2mm ~ : +/-0.76mm	76.2mm ~ : +/-0.76mm	76.2mm ~ : +/-0.76mm	-